



# [ /lommy pro T ]

## Technical Data Sheet

For tracking and Fleet Management.

### Features

- Small size, great visual performance.
- Benefits the user when settlement with customer
- Cost efficient for keeping an eye on the time consumption.

### Possibilities:

- Fleet management
- Temperature surveillance
- Remote Tacho Download
- Securing of loadspace
- Access registration

### Platform

- [www.lommyfleet.com](http://www.lommyfleet.com)  
Large Fleet Management
- White Label
- System integration (API)

### Specifications

#### Positioning and communication:

- GSM Quad band 2G - 850/900 - 1800/1900 MHz
- Triangulation: GSM
- Positioning: GSM/GPS
- RFID
- Antenna: Internal
- Communication: UDP, TCP, ftp  
RS232 port, RS485 port, CAN port
- Sensor: Movement, Temperature 1-wire ekstern
- Input: Analogue 2
- Output: Digital 1
- SD Card: Micro (Max 4GB)
- USB

#### Power:

- Power supply: 10-60Vdc
- Battery: Li-Ion - Rechargeable
- Capacity: 1150 mAh
- Lifetime: Ignition off:
  - Continuously 8 hour (1 full charge)\*
  - Movement/Interval – up to 3 months\*
  - Interval – 3 months +\*\*

#### Physical:

- Weight: 70g
- Measurement: 88x57x14mm
- Protection: IP33
- Temp. range: -30 to +60 C°

#### Certifications

- CE, E5, RoHS and WEE

#### Server and data security:

- ISAE3402 certified (referring to ISO 27002)

\*Depending on configurations

For technical questions, please contact Flextrack Support:  
[support@flextrack.dk](mailto:support@flextrack.dk)

[www.flextrack.dk](http://www.flextrack.dk)

Flextrack, Høgevej 19,  
DK-6705 Esbjerg Ø, Denmark

[ version 1.0 ]

